



PERFORMANCE SPECIFICATIONS	
COIL RESISTANCE @ 25 °C	10.1 ± 0.8 OHMS
COIL RESISTANCE @ 190 °C	16.8 ± 1.6 OHMS
SUPPLY VOLTAGE	325 VDC
CURRENT DRAW (PEAK)	2.0 AMPS
CURRENT DRAW (HOLD)	0.4 AMPS
RESPONSE TIME @ 1500 CPS	< 2.0 MSEC
RESPONSE TIME @ 5000 CPS	< 3.0 MSEC
MINIMUM FLOW @ 5000 CPS AND 600 PSI DELTA P	500 GRAMS/MIN
OPERATING TEMPERATURE	210°C (MAX)
WORKING PRESSURE	1200 PSI (MAX)
WORKING VISCOSITY	7000 CPS (MAX)

UNLESS OTHERWISE SPECIFIED:	NAME	DATE
DRAWN		
CHECKED		
ENG APPR.		
MFG APPR.		
Q.A.		
COMMENTS:		
INTERPRET GEOMETRIC TOLERANCING PER:		
MATERIAL		
FINISH		
DO NOT SCALE DRAWING		

TLX TECHNOLOGIES		
TITLE:		
CONTROL VALVE		
SIZE	DWG. NO.	REV
SCALE: 2:1	WEIGHT:	

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TLX TECHNOLOGIES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TLX TECHNOLOGIES IS PROHIBITED.