



-	-
ECO/DATE	CHANGE DESCRIPTION

PERFORMANCE SPECIFICATION:	
COIL RESISTANCE:	1.25 OHMS
SUPPLY VOLTAGE:	48 VDC
PLUNGER TRAVEL:	0.650 INCHES
SPRING PRE-LOAD	15 LBS.
LATCHING FORCE:	250 LBS MIN.
SHIFT VELOCITY:	1.30 M/SEC

SPECIFICATIONS
Material:
Heat Treat:
Remove All Burrs.
CAD File No.

TLX TECHNOLOGIES	
STANDARD DIMENSIONAL TERMS ARE: DIMENSIONS IN [] ARE IN mm ANGULAR DIMENSIONS ARE $\pm 1^\circ$	
- 1 DECIMAL POINT (.0) IS $\pm .020$ 2 DECIMAL POINT (.00) IS $\pm .010$ 3 DECIMAL POINT (.000) IS $\pm .005$ 4 DECIMAL POINT (.0000) IS $\pm .0001$ - G,D & T PER ANSI 14.5M - 125/ UNLESS SPECIFIED	
DRG SIZE	DO NOT SCALE FROM DRAWING
A	
Drawn By:	Drawn Date:
Chk By:	Chk Date:
Description	
LATCHING SOLENOID	
Drawing Number	

THIS PRINT AND THE INFORMATION THEREIN IS CONFIDENTIAL AND PROPRIETARY AND IS THE PROPERTY OF TLX Technologies. IT IS NOT TO BE COPIED OR REPRODUCED WITHOUT WRITTEN PERMISSION OF TLX Technologies.