



PERFORMANCE SPECIFICATION	
SUPPLY VOLTAGE:	28 VDC
COIL RESISTANCE@20 °C:	▽ 28.0+/-2.5 OHMS
STROKE:	▽ 0.200" +/- 0.025"
SPRING LOAD (LATCHED POSITION)	▽ 110 +/- 15 LBS.
SPRING LOAD (DE-LATCHED POSITION)	75 LBS. (REF.)
LATCHING FORCE	▽ 130 LBS. MIN.
MANUAL OVER RIDE ACTUATION FORCE:	▽ 40 LBS. MAX.

SPECIFICATIONS	
Material:	
Surface Treatment:	NONE
Remove All Burrs.	
CAD File No.	

<h1>TLX TECHNOLOGIES</h1>	
STANDARD DIMENSIONAL TERMS ARE: DIMENSIONS IN [] ARE IN mm ANGULAR DIMENSIONS ARE ± 1°	
- 1 DECIMAL POINT (.0) IS ± .020 - 2 DECIMAL POINT (.00) IS ± .010 - 3 DECIMAL POINT (.000) IS ± .005 - 4 DECIMAL POINT (.0000) IS ± .0001	
- G, D & T PER ANSI 14.5M	
125/ UNLESS SPECIFIED	
DRG SIZE	SCALE DO NOT SCALE FROM DRAWING
A	0.5:1
Drawn By:	Drawn Date:
Chk By:	Chk Date:
Description	
LATCHING SOLENOID	
Drawing Number	Revision

THIS PRINT AND THE INFORMATION THEREIN IS CONFIDENTIAL AND PROPRIETARY AND IS THE PROPERTY OF TLX Technologies. IT IS NOT TO BE COPIED OR REPRODUCED WITHOUT WRITTEN PERMISSION OF TLX Technologies.