



REV.	ECR	DATE	CHANGE DESCRIPTION
TLX TECHNOLOGIES			
STANDARD DIMENSIONAL TERMS ARE: DIMENSIONS IN [] ARE IN MM ANGULAR DIMENSIONS ARE ± 1° - 1 DECIMAL POINT (.0) IS ± .020 - 2 DECIMAL POINT (.00) IS ± .010 - 3 DECIMAL POINT (.000) IS ± .005 - 4 DECIMAL POINT (.0000) IS ± .0001 - G.D & T PER ANSI 14.5M - <input checked="" type="checkbox"/> UNLESS SPECIFIED			THIS PRINT AND THE INFORMATION THEREIN IS CONFIDENTIAL AND PROPRIETARY AND IS THE PROPERTY OF TLX Technologies. IT IS NOT TO BE COPIED OR REPRODUCED WITHOUT WRITTEN PERMISSION OF TLX Technologies.
DRG SIZE SCALE DO NOT SCALE FROM DRAWING A 2:1			Description: <h2 style="text-align: center;">LATCHING SOLENOID</h2>
Drawn By:		Drawn Date:	Drawing Number:
Chk By:		Chk Date:	Revision:

PERFORMANCE SPECIFICATION	
SUPPLY VOLTAGE:	2.4 TO 3.2 VDC
COIL RESISTANCE@20 °C:	TBD OHMS
STROKE:	2.0 MM (REF.)
SPRING LOAD: DE-ENERGIZED POSITION	3.0 N (REF.)
NET PULL FORCE:	TBD
OPERATING TEMPERATURE:	-20°C TO 107°C
VALVE SEAT MATERIAL:	NBR RUBBER
DURABILITY:	1M CYCLES MIN.

SPECIFICATIONS	
Material:	
Surface Treatment:	
Remove All Burrs.	
CAD File No.	