



PERFORMANCE SPECIFICATIONS	
STROKE	< 0.25 inch (<6.4 mm)
LATCHING FORCE	10 lbs. (44 N)
RESPONSE TIME	< 8 msec
CENTERING FORCE	3 ± 1 lb. (13 ± 4 N)
CURRENT	12 amps max
DURABILITY	> 100M cycles
COIL RESISTANCE	5 Ω

**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TLX TECHNOLOGIES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TLX TECHNOLOGIES IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE
DIMENSIONS ARE IN INCHES	DRAWN		
TOLERANCES:	CHECKED		
ANGULAR: 1°	ENG APPR.		
TWO PLACE DECIMAL ±.01	MFG APPR.		
THREE PLACE DECIMAL ±.005	Q.A.		
INTERPRET GEOMETRIC TOLERANCING PER:	COMMENTS:		
MATERIAL			
FINISH			
DO NOT SCALE DRAWING			

<b>TLX TECHNOLOGIES</b>		
TITLE:		
<b>THREE POSITION LATCHING SOLENOID</b>		
SIZE	DWG. NO.	REV
<b>B</b>		
SCALE: 2:1	WEIGHT:	SHEET 1 OF 1